

### 水務署

#### Water Supplies Department

香港灣仔告士打道七號入境事務大樓 Immigration Tower, 7 Gloucester Road, Hong Kong

電子郵遞 e-mail

wsdinfo@wsd.gov.hk

電 Telephone

2829 4355

圖文傳真 Facsimile

2824 0578

(2) in WSD 3321/17 Pt.1 T/J(23) Reference

9 February 2017

**E&I** International Limited 8/F., Block B, Chung Mei Centre, 15 Hing Yip Street, Kwun Tong, Kowloon, Hong Kong

(Attn.: Ms Fanny YAU)

Dear Madam,

#### Approval of "BELLINI" Sensor Flush Valve

Your letter ref. FY170109A dated 9 January 2017 refers.

Having considered the test report ref. J21126A issued on 6 January 2017 by Nutek Systems (HK) Limited, this Authority accepts that the fitting described below complies with, and its use when correctly installed does not contravene, the Waterworks Ordinance and Regulations.

Name of Manufacturer:

**E&I** International Limited

**Country of Origin:** 

China

**Brand:** 

Bellini

**Details of Fitting:** 

1/2" Urinal sensor flush valve

Model:

BL/GL-8688B

**Body Markings:** 

**Expiry Date:** 

3 January 2022

Proviso:

As the fitting has not been tested for use in contact with water intended for human consumption, the fitting can only be used in flushing water plumbing system.

This Authority hereby permits the use of the above fitting in flushing water plumbing systems subject to full adherence to Waterworks installation requirements. In particular, you are required to draw your customers' attention to the following requirement-

"Installation of filter before flushing valve is required. Without the filter, the flushing valve is liable to leak. The installed filter need frequent inspection and cleaning to maintain flushing supply. Normally only public toilets with good management system for maintenance would be considered."

"A stop cock or gate valve must be installed at the upstream of the fitting for manual isolation of water supply."

"The design flushing volume of the flushing valve should be compatible with the toilet bowl to ensure that effective clearance can be achieved by a single flush of water."

"Flushing valve should be used within the range of working pressures specified by the manufacturer." AND

"Installation of electronic opening and closing sanitary tapware should also comply with the requirements of Electrical & Mechanical Services Department."

A condition of this acceptance is that the fitting to be installed shall be replicas of the sample as certified by the testing agent mentioned above and without modifications. This acceptance may be withdrawn at any time if the standard of the fitting installed fails to meet that of the approved sample or if the fitting is found to be unsuitable for use in flushing water plumbing systems.

For the use of the fitting in any project, the Acceptance Reference Number at the bottom of this letter must be quoted as a means of identification of acceptance of the fitting by this Authority.

Should you have any enquiries, please contact our Engineer Mr Terry KUNG at tel. no. 2294 2656.

Yours faithfully,

(CHAN Chung Kun) for Water Authority

c.c.

WSD 3321/1/82 ] - without catalogue

ME/MC

] - with soft copy only

註冊號碼 (Registration No.):



## 自願參與用水效益標籤計劃 - 小便器用具 Voluntary Water Efficiency Labelling Scheme - Urinal Equipn



This is to certify that

# **E&I International Limited**

Labelling S.將下列小便器用具在本計劃內註冊:

has registered the following urinal equipment under this sch

BL/GL-8688E

/ Category

在用水效益標籤上展示的標誌

Symbolic Presentation on the Water Efficiency Label Water droplet(s)

用水效益級別

Water Efficiency Grade

沖水量 Water Flush Volume

簽發日期: 12 June 2017 Date of Issue:





滴水點

水務署署長(周世威代行)

工程,使用力类类有自能划能,业且能建至银外即自用水。 The above urinal equipment is operated with a smart demand operation to achieve additional water saving: